

Secvest Wireless Indoor Sounder

Art.-Nr. FU8230



- For acoustic support of the alarm panel and wireless outdoor siren
- Rugged injection-moulded ABS housing
- Loud signal generator
- Any number of indoor sirens can be used with the Secvest 2WAY/IP
- Any number of indoor sirens can be used with the Secvest 2WAY/IP

The Secvest wireless indoor sounder is an optional accessory for the Secvest 2WAY. As a purely acoustic signalling unit, it supports the wireless outdoor siren and the alarm panel of the Secvest 2WAY with a 90 dB tone. The sounder and the alarm panel communicate on 868.6625 MHz, a radio frequency specially reserved for security purposes. The wireless indoor sounder can be powered by batteries or power supply. When using batteries, the service life is approx. 2 years. A weakening battery is indicated on the sounder.

Technical Data

Battery type	3x 1.5V LR20 battery
Connections	12V
DC voltage supply	4,5/12V
Environmental class	II
Height	208mm
Housing material	ABS
IP protection class	54
Installation location	Indoors
Length	60mm
Max. battery life	2year(s)
Max. humidity	75%

Max. operating temperature	50°C
Max. receiving range (building)	30m
Max. receiving range (outdoors)	100m
Min. operating temperature	-10°C
Modulation	FM
Radio frequency	868,6625
Sound pressure	90dB
Voltage monitoring	Yes
Width	122mm