

Key switch incl. ABUS quality cylinder

Art.-Nr. SE1010



- Easy installation and operation
- Easy to activate and deactivate by turning key
- For on-wall mounting
- High security thanks to core extraction protector as well as cover and wall sabotage switch
- Sturdy housing

Use the surface mount key-switch to arm and disarm your alarm system. Simply turn the key instead of entering a PIN code. Operating your system is faster and easier. Apart from the arm/disarm function of the alarm system (or individual partitions), you can use the surface mount key-switch to control electronic equipment (entrance lighting, garage door, etc.). Two switch contacts are provided. You can set these as a permanent contact or as a pulse generator. The two colored LEDs permanently inform you about the state of connected devices. For example, you can see if the system is currently armed or disarmed. The reinforced fascia plate, the high-quality ABUS cylinder and a robust weatherproof housing (IP 55) protect the key-switch against external influences. The surface mount key-switch is designed for half-cylinders (10/30). It is available for both surface and flush fitting. The surface-fitted variant is protected from tampering by a cover contact and an anti-removal wall contact.

Technical Data

DC voltage supply	10-15V
Height	87mm
Housing material	ABS
IP protection class	55
Installation location	Surface fitting
Length	55mm

Power consumption	2mA
Power consumption	0,02
Status display	Yes (2 LEDs)
Tamper monitoring	Yes
Width	117mm