

IR Illuminator S - 850 nm, 30°, 20 m

Art.-Nr. TVAC71010



- Integrated photo sensor for automatic activation and deactivation
- Variable power supply input 12-24 AC/DC
- Semidiscreet for long ranges
- Range up to 20 m
- IP66 for indoors and outdoors

More light – better images

In order to record clear images even in the dark, the cameras need (infrared) light. The semidiscreet S IR illuminator provides cameras with the light they need even in absolute darkness. The IR LEDs provide infrared light with a wavelength of 850 nm for night-time recordings. The IR illuminator is suitable for both black and white and day/night cameras.

Also for use in extreme weather conditions

The range of the IR illuminator depends on the light sensitivity of the camera. At 0.1 lux, the range is about 20 metres, at 0.01 lux it is up to 40 metres. The radiation angle is 30° (horizontal). The S IR illuminator is dustproof and protected against strong jets of water (IP66). It can therefore be used without problems outdoors at temperatures between -30°C and +40°C. Its maximum power consumption is 6 watts.

Automatic day/night switching – semidiscreet LEDs

Using its built-in photo sensor, the IR illuminator detects the onset of darkness and switches on automatically. When the brightness is sufficient, for example in daylight, it switches itself off. The S IR illuminator 850 nm 30° is a semidiscreet IR illuminator. The wavelength of this illuminator is approximately 880 nm, slightly shorter than the wavelength (940nm) of a discreet illuminator of the same type. The advantage of a semidiscreet illuminator is its greater range. Only in the immediate vicinity of the S illuminator is the reddish glow of its LEDs slightly visible.

The variable 12-24 AC/DC power input means the IR illuminator can be powered with an AC or DC supply.

IR Illuminator S - 850 nm, 30°, 20 m

Art.-Nr. TVAC71010

Technical Data

AC voltage supply	12 - 24 VACV
Arming	< 3 Lux
DC voltage supply	12 - 24 VDCV
EAN	4043158056297
Height	49mm
Horizontal/vertical IR angle	30°
Housing material	Aluminium
IP protection class	66
Length	55mm
Max. operating temperature	40°C

Min. operating temperature	-30°C
Mount	M6 thread
Net weight	0,35kg
Optical wavelength	850nm
Power consumption	6W
Power consumption	max. 0,5 AmA
Range at 0.01 lux	20mm
Width	85mm