

IR Illuminator M - 850 nm, 30°, 30 m

Art.-Nr. TVAC71060



- Integrated photo sensor for automatic activation and deactivation
- Variable power supply input 12 - 24 AC/DC
- Semidiscreet for long ranges
- Range up to 30 m
- IP66 for indoors and outdoors

More light – better images

In order to record clear images even in the dark, the cameras need (infrared) light. The semidiscreet M IR illuminator – 850 nm provides cameras with the light they need even in absolute darkness. The 21 LEDs provide infrared light with a wavelength of 850 nm for night-time recordings. The IR illuminator is suitable for both black & white and day/night cameras.

Also for use in extreme weather conditions

The range of the IR illuminator depends on the light sensitivity of the camera. At 0.1 lux, the range is about 30 metres, at 0.01 lux it is up to 60 metres. The radiation angle is 30° (horizontal). The M IR illuminator is dustproof and protected against strong jets of water (IP66). It can therefore be used without problems outdoors at temperatures between -30 °C and +40 °C. Its maximum power consumption is 8 watts.

Automatic switching – semidiscreet LEDs

Using its built-in photo sensor, the IR illuminator detects the onset of darkness and switches on automatically. When the brightness is sufficient, for example in daylight, it switches itself off. The M IR illuminator 850 nm 30° is a semidiscreet IR illuminator. The wavelength of this illuminator is approximately 880 nm, slightly shorter than the wavelength (940 nm) of a discreet illuminator of the same type. The advantage of a semidiscreet illuminator is its greater range. Only in the immediate vicinity of the illuminator is the reddish glow of its LEDs slightly visible.

The variable 12-24 AC/DC power input means the IR illuminator can be powered with an AC or DC supply.

IR Illuminator M - 850 nm, 30°, 30 m

Art.-Nr. TVAC71060

Technical Data

AC voltage supply	12 - 24V
Arming	< 3 Lux
DC voltage supply	12 - 24V
EAN	4043158056341
Height	69mm
Horizontal/vertical IR angle	30°
Housing material	Aluminium
IP protection class	66
Length	70mm

Max. operating temperature	40°C
Min. operating temperature	-30°C
Mount	M6 thread
Net weight	0,45kg
Optical wavelength	850nm
Power consumption	8W
Power consumption	max. 700mA
Width	85mm