

Outdoor IR VGA WLAN network camera

Art.-Nr. TVIP60550



- VGA resolution: 640 × 480 @ 25 fps
- Weatherproof camera housing (IP54)
- Day/night switching with electromechanical IR swivel filter (ICR)
- IR LEDs for night vision
- Quad stream (H.264, MPEG-4, MJPEG, 3GPP)
- WLAN n standard

The IR VGA WLAN network camera is a VGA network camera that has been specially developed for efficient front door video surveillance. Thanks to protection class IP54, it can also be used in covered outdoor areas without any additional protective housing. It supplies color images with a resolution of up to 640 x 480 pixels. Video data is transmitted wirelessly via WLAN. Full-resolution images are transmitted in real time (25 frames/second). At the same time, video data can be stored in the 4-channel video buffer in the local network through the LAN/WLAN connection on the router. With a 53.1° angle of view, the camera can capture much more than the door area when positioned accordingly. Legally sensitive areas of the image can be hidden using privacy masking. With its high light sensitivity, automatic day/night switching with IR swivel filter, 12 integrated IR LEDs, and image correction functions such as BLC, AGC, or AWB, the camera always delivers perfect recordings in both changing light conditions and darkness.

Outdoor IR VGA WLAN network camera

Art.-Nr. TVIP60550

Technical Data

Alarming	HTTP, SMTP, FTP, network drive, e-mail
Amplifier control	AGC
Backlight compensation	BLC
Camera type	Day/night
Certifications	CD, RoHS, C-Tick
DC voltage supply	12V
Day/night switching	IR cut is swivelled electromagnetically
Digital zoom	4
Electronic shutter	1/5, 1/15, 1/30
Encryption	HTTPS, WEP, WPA-PSK, WPA2-PSK
Focal length	4,0mm
Frame rate	MJPEG: 25 frames/s @ 640x480, MPEG-4: 25 frames/s @ 640 x 480, H264 25 frames/s @ 640 x 480fps
Height	73mm
Horizontal angle of view	53,1°
IP protection class	54
IR LEDs	12
IR range	10m
Image sensor	1/4" Progressive Scan CMOS
LAN network access	RJ45
Length	200mm
Lens	F1.5, 4.0mm
Max. operating temperature	50°C
Max. resolution @ frame rate	640 x 480 @ 25 fps

Min. operating temperature	-10°C
Minimum illumination (IR)	0
Minimum illumination (color)	0.8
Motion detection	3 zones
Network camera protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, TRSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP and 802.1X
Number of streams	H.264, MPEG-4, MJPEG
Pixels (effective)	640(H) x 480(V)pixel
Pixels (total)	640(H) x 480(V)pixel
Power consumption	300mA
Power consumption	3.6W
Pre-alarm/post-alarm memory	7 pre-alarm images, 1 event image, 7 post-alarm images
Private zones	yes
Resolution modes	640 x 480pixel
Video compression	H.264, MPEG-4, MJPEG
WLAN network access	802.11 b/g/n
White balance	yes
Width	73mm